

# FAG



## FAG SmartCheck

Machinery monitoring for every machine

SCHAEFFLER





## Foreword

Increasing competition leads to increased cost pressures and drives companies to reduce their maintenance costs.

It is therefore vital to avoid unplanned downtime and maximise machine lifetime.

In expensive plant in the steel and paper industries, for example, rolls and the associated bearing arrangements have therefore been fitted for many years with complex and costly continuous online monitoring systems.

In the case of standard machines such as pumps, fans and gearboxes, continuous monitoring is often not applied since an affordable online solution has not been available so far.

FAG SmartCheck is a cost-effective, innovative online measuring system for the continuous monitoring of machine and process parameters on a decentralised basis. It offers the performance features of expensive systems but is compact in design, easy to fit and simple to use.

The system can be expanded on a modular basis and can thus be adapted at any time to meet changing requirements.



# Contents

	Page
<b>Features</b>	
Operation and communication .....	5
Function .....	5
Application .....	7
Concept .....	9
Software .....	10
Service .....	13
<b>Technical data</b>	
FAG SmartCheck .....	14

# FAG SmartCheck

- Features** FAG SmartCheck is an innovative online system that can be used on numerous machines.
- FAG SmartCheck has numerous advantageous features including:
- small and robust
  - cost-effective
  - intuitive operation
  - expandable
  - comprehensive information on machine condition taking account of process parameters such as:
    - load
    - pressure
    - flow rate
  - information available on the long term development of machine condition by means of the integrated data memory
  - connection to control room or controller by means of interfaces
  - reliable alarm system by means of an alarm threshold adjustment system applied for as a patent
  - direct system access via Ethernet and Web interface
  - protected data by means of a multistage access concept
  - free of charge app for smartphones
  - complete service for rolling bearings and for machinery diagnostics.

## Operation and communication

FAG SmartCheck can be used easily and on an intuitive basis by means of two capacitive keys.

Due to the software FAG SmartWeb integrated in the device, it can be accessed via a Web interface using any standard browser.

The device can be connected via interfaces to, for example, a controller, control room or PC, *Figure 1*.

- ① Status LED, red, yellow, green
- ② Membrane key, alarm reset
- ③ Membrane key, activate teach mode
- ④ Interface: Ethernet, power supply, PoE
- ⑤ Interface: RS485, power supply
- ⑥ Interface: inputs and outputs, analogue and digital

*Figure 1*  
LEDs, keys and interfaces



## Function

FAG SmartCheck is ready for immediate use as soon as it is delivered. The integrated characteristic value set allows general, reliable monitoring.

For more precise monitoring, a component template stored in the device can be selected for applications such as fans or pumps. The component template is filled with the component data. The device has an integrated rolling bearing database containing data for FAG and INA standard bearings. The user can add further rolling bearings to the database at any time.

Depending on the component template selected, certain parameters can be adjusted, such as:

- bearing type
- number of fan blades
- gear teeth
- belt lengths.

The characteristic value set thus generated allows highly precise monitoring of the machine.

# FAG SmartCheck

- Configuration** With one FAG SmartCheck, it is possible to monitor several components of a machine at the same time. A separate configuration can be generated using wizards by means of a Web browser. Several component templates are combined in an overall configuration for the machine to be monitored. This configuration can be copied to any number of devices required.
- Monitoring** Vibrations and process parameters such as pressure and flow rate are determined and correlated.
- Alarm system** The automatic alarm threshold adjustment, for which a patent has been applied, allows a reliable alarm system. An alarm is indicated immediately by an LED on the device. The alarm can be transmitted to the control room by means of interfaces. A free of charge app can convert any smartphone into an alarm receiver on a WLAN network, *Figure 2*.




*Figure 2*  
Smartphone as alarm receiver



## Application

The device detects damage to a wide variety of machines at an early stage. A selection is shown in *Figure 3*.



*Figure 3*  
Monitored machines

# FAG SmartCheck

**Standard templates** The standard templates in FAG SmartCheck detect the following damage:

- rolling bearing damage
- imbalance
- misalignment
- impacts.

**Expanded monitoring** The user can apply the standard templates for monitoring. He also has the option of using templates for specific machines. Specific damage patterns are detected precisely and can be allocated to a component. Examples are shown in the table.

## Templates for specific machines

Machine	Characteristics identified using template for specific machines
Electric and geared motors	Winding damage and loose rotor bars
Vacuum and fluid pumps	Wear and cavitation
Ventilators and fans	Blade and vane rotational frequencies
Compressors	Changes to the typical vibration pattern
Gearboxes	Tooth set damage
Separators and decanters	Cavitation, floating imbalance between screw and drum
Vibrating screens	Settling of screen mats, loose springs, spring breakage

## Concept

Monitoring using FAG SmartCheck can be carried out in three stages. In the first stage, individual machines are monitored on a decentralised basis. If the user selects the second stage, the device is intelligently integrated in the machine controller. In the third stage, the service is provided from a single source by an external service provider. This can include remote access via an Internet connection as well as advice and other services, *Figure 4*.

- ① Decentralised machinery and process monitoring
- ② Intelligent process integration
- ③ Service from one source

*Figure 4*  
Multistage concept



### Decentralised machinery and process monitoring

Installation and cabling of FAG SmartCheck is a simple process. The device is ready for immediate use. Data can be accessed directly from the device.

### Intelligent process integration

Intelligent process integration is the option of communication via interfaces. During communication, data are exchanged with, for example, a PLC or control station. User-specific integration in bus systems can be achieved, for example, by means of an RS485.

### Service from one source

The Web interface for FAG SmartCheck allows remote access to measurement data via an Internet connection. Monitoring can thus be outsourced to an external service provider.

# FAG SmartCheck

**Software** Each FAG SmartCheck includes the integrated software FAG SmartWeb. The device can be accessed by means of FAG SmartWeb using any Web browser.

The software FAG SmartUtility light is a free of charge PC software. The software can be used to configure the Web address, save data and update firmware.

The paid-for PC software FAG SmartUtility allows unrestricted access to all the functions in FAG SmartCheck, see table.

## Functional scope

Function	SmartWeb	SmartUtility light	SmartUtility
Display characteristic value status	●	–	○
Display system information	●	–	○
Display measurement data	●	–	○
Display trend	●	–	○
Select component templates	●	–	○
Configure inputs and outputs	●	–	○
Configure and activate validator	●	–	○
Configure and activate trigger	●	–	○
Configure user administration	●	–	○
Display input signals in real time	●	–	○
Configure TCP/IP settings	–	●	●
Update firmware	–	●	●
Download and save data	–	●	●
Analyse data	–	–	●
Manage all FAG SmartCheck devices in the network	–	–	●
Load and send configurations	–	–	●

- Executed by this software
- Not supported by this software
- Can be called up, will be executed by FAG SmartWeb

The use of FAG SmartUtility light and FAG SmartUtility requires a Windows PC, see hardware requirements in table, page 15.

**Data analysis** FAG SmartCheck offers extensive possibilities for analysing measurement data and assessing the condition of the machine being monitored.

The following general characteristic values are determined from the acceleration and acceleration envelope signal:

- RMS, broadband
- RMS, frequency-selective
- peak-to-peak value
- crest factor
- periodic value
- W-count
- temperature.

FAG SmartCheck does not, however, only calculate the general characteristic values. In addition, the component templates integrated in the device offer frequency-selective monitoring matched to various components.

Characteristic patterns in components such as shafts, belt pulleys or fan wheels indicate incipient damage at an early stage.

In conjunction with process parameters such as torque, load or speed, it is possible to make precise statements relating to the damage progress.

# FAG SmartCheck

## Presentation of trends

Presentation of trends is a simple and authoritative presentation of characteristic values. A change in the vibration behaviour can be detected at a glance. Even slight changes are visible in the trend pattern, *Figure 5*.



① Presentation of trends and signals over 5 months

*Figure 5*  
Viewer presentation

## In-depth analysis

For this analysis, the Viewer function in FAG SmartUtility is used. The Viewer offers numerous tools that assist the experienced user in carrying out analysis.

## Alarm threshold adjustment

In the delivered condition, FAG SmartCheck uses preset alarm thresholds. The vibrations in a machine are decisively influenced by the specific operating condition. In order to adjust the alarm thresholds to match the specific machine, FAG SmartCheck has an automatic teach mode.

The user must start the teach mode at the time of first operation. The associated vibration value is then measured and allocated for each operating condition of the machine. Based on the measurement data for vibrations and process values, FAG SmartCheck determines the correct alarm thresholds itself. The dependence of vibrations on several process values is also taken into consideration.

As soon as sufficient measurement data are available, FAG SmartCheck automatically substitutes the newly determined alarm thresholds for the preset values.

Through the multi-dimensional adaptation of alarm thresholds, critical machine conditions are identified and reliable alarm operation in every machine condition is ensured.

- Service** Schaeffler offers extensive services ranging from strategy development through first operation to remote monitoring.
- First operation** In partnership with the customer, the suitable monitoring strategy is determined, devices are mounted and reference measurements are carried out.
- Training courses** Employees are trained as a function of their prior knowledge and requirements. The training covers handling of the device and use of the software.
- Operation** We are pleased to offer our experience at any time. For example, our experts can assist in the assessment of measurement results. If the measurement results indicate any damage, they can provide advice on further action.
- Remote monitoring** If the necessary expert knowledge is not available or trained employees are not present on site, remote monitoring may be advantageous, *Figure 6*.



*Figure 6*  
Remote monitoring  
with data evaluation by Schaeffler

If Schaeffler is tasked with remote monitoring, the customer receives regular reports on the machine condition and recommended actions for improving plant availability. If FAG SmartCheck detects incipient damage, the customer is informed immediately. Repair can then be planned and replacement parts sourced in good time. Further information can be found at [www.FAG-SmartCheck.com](http://www.FAG-SmartCheck.com) or by simply contacting us.

# FAG SmartCheck

FAG SmartCheck	
Features	Description
Size (W×H×D)	44 mm×57 mm×55 mm
Mass	≈ 210 g
Housing material	Glass fibre reinforced plastic
Fixing method	Screw M6
	Contact surface on the machine: ∅ 25 mm
Protection class	IP 67
Power supply	DC 11 V to DC 32 V
	Power over Ethernet
Maximum power consumption	200 mA at 24 V
Operating temperature	-20 °C to +70 °C
Operating system	Embedded Linux
Software (languages: German, English, Chinese)	FAG SmartWeb (Internet Explorer, Firefox)
	FAG SmartUtility light

## Memory

Features	Description
Program and data memory	64 MB RAM, 128 MB Flash

## Interfaces

Features	Description
Control elements	2 keys for teach mode, alarm reset, restart, default settings
Display elements	1 LED for status and alarm display
	1 LED for confirmation of keys
	2 LEDs for communication display
Communication	Ethernet 100 MB/s RS485
Electrical connections	3 polarity protected M12 push-fit connectors for power supply, RS485, analogue and digital inputs and outputs, Ethernet

Internal vibration sensors	
Features	Description
Piezoelectric accelerometer	25 mV/g
Frequency range	0,8 Hz to 10 kHz
Measurement range	± 50 g
Resolution	200 µg

## Measurements

Features	Description
Measurement functions	Acceleration, velocity and displacement by integration
	Temperature and process parameters such as speed, load and pressure
Diagnostic methods	Time signal, envelope curve
	Speed and frequency tracking
	Spectrum and trend analysis
Characteristic values in time and frequency range	Defined characteristic values: DIN ISO 10816
	Calculated characteristic values: RMS, frequency-selective RMS, DC, peak, peak-to-peak, crest factor, W count, condition guard
Special features	Other user-defined characteristic values are possible



# FAG SmartCheck

Signal processing	
Features	Description
Frequency resolution	1 600 lines, 3 200 lines, 6 400 lines, 12 800 lines
Measurement accuracy	24 Bit, A/D converter
Frequency range	0,8 Hz to 10 kHz
Low pass filter	50 Hz to 10 kHz Stages: 50 Hz, 100 Hz, 200 Hz, 500 Hz, 1 kHz, 2 kHz, 5 kHz, 10 kHz
High pass filter, envelope curve only	750 Hz, 1 kHz, 2 kHz
Special features	Other filters available by agreement

Inputs and outputs	
Features	Description
Inputs	2 analogue inputs, 12 Bit, frequency range 0 Hz to 500 Hz:
	Voltage: 0 V to 10 V, 0 V to 24 V
	Input resistance: 10 k $\Omega$
	Current: 0 mA to 20 mA, 4 mA to 20 mA
	Input resistance: 500 $\Omega$
1 pulse input:	0 V to 30 V, 0,1 Hz to 50 kHz
Outputs	1 analogue output, 12 Bit:
	Voltage: 0 V to 10 V
	Minimum load resistance: 1000 $\Omega$
	Current: 0 mA to 20 mA, 4 mA to 20 mA
	Maximum load resistance: 250 $\Omega$
1 switching output:	Open collector, max. 1 A, 30 V
Special features	Electroplated separation between inputs and outputs

Accessories	
Ordering designations	Description
<b>SMART-CHECK.CABLE-POW-P-M12-OE-10M</b>	Power cable: 10 m, 8 pin, M12 socket on free connection end
<b>SMART-CHECK.CABLE-ETH-P-M12-RJ45-10M</b>	Ethernet cable: 10 m, M12 plug on RJ45
<b>SMART-CHECK.CABLE-IO-P-M12-OE-10M</b>	Input/output cable: 10 m, 8 pin, M12 plug on free connection end
Special features	Other accessories available by agreement

Software	
Features	Description
<b>SMART.UTILITY</b>	Paid-for PC software for system management

Hardware for use of FAG SmartUtility and FAG SmartUtility light	
Features	Description
System architecture	Windows
Processor	Pentium III or higher
Processor speed	600 MHz (recommended 1 GHz)
RAM	2 GB (recommended 4 GB)
Screen resolution	At least 1 024×768, font size normal
Free space on hard disk	40 MB

# FAG SmartCheck

Product variants	
Ordering designations	Description
<b>SMART-CHECK</b>	FAG SmartCheck including Web interface, FAG SmartWeb and PC software, FAG SmartUtility light
<b>SMART-CHECK-KIT-003</b>	1×FAG SmartCheck with accessories (starter configuration, cable and basic manual)
<b>SMART-CHECK-KIT-005</b>	End customer starter kit: 5×FAG SmartCheck including accessories
<b>SMART-CHECK-KIT-008</b>	OEM/OES starter kit: 5×FAG SmartCheck including accessories
Special features	Other product variants available by agreement

Services	
Ordering designations	Description
<b>SMART-CHECK-SERVICE-001</b>	Preparation of application-specific or machine-specific monitoring strategy in consultation with customer
<b>SMART-CHECK-SERVICE-002</b>	Preparation of monitoring configuration based on templates in FAG SmartCheck
<b>SMART-CHECK-SERVICE-005</b>	Mounting and first operation of FAG SmartCheck
<b>SMART-CHECK-SERVICE-006</b>	Data collection from FAG SmartCheck, analysis and reporting including recommended actions
<b>SMART-CHECK-SERVICE-014</b>	E-service including evaluation of conspicuous measurement data and reporting including recommended actions
<b>SMART-CHECK-SERVICE-007</b>	Starter kit service for end customers: 16 service hours, content to be selected individually, for example general advice, system instruction, local support and other services
<b>SMART-CHECK-SERVICE-009</b>	Starter kit service for OEM/OES: 24 service hours, content to be selected individually
Special features	Other services available by agreement



**Schaeffler Technologies  
AG & Co. KG**

Postfach 1260  
97419 Schweinfurt  
Germany

Georg-Schäfer-Straße 30  
97421 Schweinfurt  
Germany

Phone +49 2407 9149-66  
Fax +49 2407 9149-59  
E-Mail [industrial-services@schaeffler.com](mailto:industrial-services@schaeffler.com)  
Internet [www.schaeffler.com/services](http://www.schaeffler.com/services)

Every care has been taken to ensure the correctness of the information contained in this publication but no liability can be accepted for any errors or omissions. We reserve the right to make technical changes.

© Schaeffler Technologies AG & Co. KG  
Issued: 2012, March

This publication or parts thereof may not be reproduced without our permission.

TPI 214 GB-D